

Please ~~REPLACE~~ the paragraph beginning at page 2, line 11, with the following:

A2
--EP-A-0 820 203 shows a method and an arrangement for making use of resources in a telecommunications network. This arrangement/method is however not satisfactory for several reasons. For example, it does not satisfactorily take into account the time that a resource exists. To do that, attributes have to be added containing information about time of existence. However, this would have to be done for every resource to make it meaningful, which would considerably reduce the performance.--

A3
Please ~~REPLACE~~ the paragraph beginning at page 7, line 19, with the following:

--The concept of resources is used in order to have a concept for all "real" things in the system. It is very important to distinguish between two things, resource creation, e.g., installation of a new telephone line, and resource allocation, e.g., changing the state of an existing telephone line from unused to used.--

A4
Please ~~REPLACE~~ the paragraph beginning at page 10, line 11, with the following:

--In a particular implementation the database arrangement comprises fields enabling the use of a regular code (e.g. C, JavaTm) if needed, which gives a high flexibility. According to the invention every resource does not necessarily have an (explicit) connection.--

A5
Please ~~REPLACE~~ the paragraph beginning at page 12, line 10, with the following:

--A simplified view of the flow of information is that a Common Service Description Layer (CSDL) command is sent by the SRP 14 to SARM 18 where it is translated to an Atomic Service Description Layer ASDL command and routed to SRIM 19. The SRIM 19 then asks STDB 17 and SRDB 16 for additional information, which is used to make a new CSDL command that is translated to an ASDL command and routed to the NEP 15. The response from the NEP 15 follows in principle the same way backwards, where return status and data is used to update the SRDB 16.--

Please **REPLACE** the paragraph beginning at page 13, line 11, with the following:

AG
--In step 2, assuming that the customer wants the product or service (a product is used by example below), a feasibility check is made to check if it is possible to implement the product or service with the existing conditions, i.e. if all prerequisites are fulfilled. Now a "call" for this code is made. As the execution starts, this code uses the product type input to look in the Product type hierarchy. By looking here it is possible to find out which (sub)products the DuoCom product is composed of. In this case the four product types ISDN Access, E-mail, Personal Homepage and 020-connection will be found. As they in turn may consist of additional, more simple products, the Product type hierarchy is once again examined to see if the new products have sub products and so on until no more product types are found.--

AT
Please **REPLACE** the paragraph beginning at page 13, line 26, with the following:

--As some of the (sub)products may be optional, i.e., the end customer has to be asked which (sub)product is desired and informed about the possible choices. This results in an interactive loop in which the customer picks the desired (sub)products. As these (sub)products are selected, the Product type operation parameters and the Product type parameter tables are examined to find out which parameters are needed. As this selection of (sub)products is dynamic to its nature, the Product type relations table is examined to check that combinations of incompatible product types are not accidentally created. When this loop has ended, the Product type prerequisites and the Product type resource prerequisites tables are examined with regard to Product instance data and resource data, if the sufficient amount of resources or existing product instances are available, so that it is possible to instantiate this new product instance.--

Please **REPLACE** the paragraph beginning at page 14, line 29, with the following:

AS
Cm.T
--All data is stored in a relational database(s), see FIG. 4 which shows the table names and the fields in each table that has relations to/from them together

A8
Cmell.

with the relationship type, e.g., 1, n is one-to-many. The tables may be created by reading from standard text files with SQL commands.--

Please ~~REPLACE~~ the Abstract with the following:

A9
--A resource handler for use in an operational support structure for managing a telecommunications network. The handler includes a service and resource database containing information regarding network resources. The database arrangement is structured so that each resource in the network has a time of existence as well as a place in a hierarchy of parent/child relations. The resource is defined by the following data: a point identifier that has characteristics associated with it, in the form of an abstract description of the resources capabilities; an abstraction of a common network element represented by a group of points that are considered to belong together, and a connection, which is defined by two connected points.--

A10
Please ~~ADD~~ the following paragraphs to the application after page 14, line 32:

--It should be emphasized that the terms "comprises" and "comprising", when used in this specification as well as the claims, are taken to specify the presence of stated features, steps or components; but the use of these terms does not preclude the presence or addition of one or more other features, steps, components or groups thereof.

Various embodiments of Applicants' invention have been described, but it will be appreciated by those of ordinary skill in this art that these embodiments are merely illustrative and that many other embodiments are possible. The intended scope of the invention is set forth by the following claims, rather than the preceding description, and all variations that fall within the scope of the claims are intended to be embraced therein.--